

# Product Data Sheet

Care emulsion for refreshing oiled wood floors

# MAGIC OIL CARE

Water-based oil emulsion for refreshing and maintaining impregnating oiled wood floors. With refresher effect.

## PRODUCT DESCRIPTION:

MAGIC OIL CARE has components which produce a “topping up” effect. This effect provides lasting care and protection. Dependant on dilution and frequency of application during the maintenance programme, the intervals for deep cleaning and re-treatment are extended.

### Care tip:

In order to extend the life span of an impregnated wood flooring, a professional, thorough, periodic clean and specialist re-treatment is essential. The exact care instructions and further information can be obtained from your floor installer.

## AREA OF APPLICATION:

Care product for maintenance-cleaning of oiled wood floors treated with products of the MAGIC OIL Line or SOYABASE PLUS.



## PRODUCT BENEFITS / PROPERTIES:

- ▶ moisturizing effect
- ▶ sustainable care

## TECHNICAL DATA:

Packaging:	plastic container
Packsize:	0,75 and 5 l
Color:	transparent, white
Consumption:	Maintenance care: approx. 250 ml/5 l water until pure
Working climate:	between 18 – 25 °C and 35 – 65 % relative humidity
Walkable:	immediately after drying

The mixing ratio depends on the degree of soiling from 250 ml to 5 litres of water, until pure application.

## SURFACE PREPARATION:

Remove traces of dirt and dust by using the PALLMANN MOP, broom or vacuum cleaner. In case of heavy surface soiling, an intensive clean must be carried out.

## APPLICATION:

1. Carry out routine cleaning with PALLMANN CLEAN (see current product data sheet on [www.good-for-woods.com](http://www.good-for-woods.com)).
2. Before use, the container must be brought to room temperature (20 °C) and must be shaken well.
3. Dilute approx. 250 ml PALLMANN MAGIC OIL CARE with 5 liters of water. In case of heavy soiling increase concentration, if necessary use up to undiluted. Apply evenly in one direction using the damp (not wet) PALLMANN MOP and let dry.
4. After drying (approx. 1 hours) the surface can be put back into use.
5. After use, clean tools with water.
6. The exact maintenance and care routine is shown in the respective care instruction.

## IMPORTANT NOTES:

- ▶ Optimum temperature is 18 to 25 °C with the relative humidity > 35 % and < 65 %. Low temperatures and high humidity will extend the drying time. High temperatures and low humidity will shorten the drying time.
- ▶ Shelf life minimum 24 months in original packaging when stored in dry conditions. Protect from freezing and do not expose to temperatures over 40 °C.
- ▶ Tightly reseal opened containers.
- ▶ When using our care products, especially on factory finished floors, and in rare cases there may be some appearance differences. We therefore recommend to create a small sample area in advance to check compatibility.
- ▶ Flecks and applicator marks can be removed with PALLMANN CLEAN on a cloth or non-scratch PALLMANN CLEANING PAD WHITE.
- ▶ Leave freshly oiled surfaces until fully hardened before treating with PALLMANN MAGIC OIL CARE.
- ▶ Regular maintenance with PALLMANN MAGIC OIL CARE improves the appearance and increases the wear life of the oiled surface.
- ▶ The following standards and notices are applicable and especially recommended: DIN 18356 "Working with parquet and woodblocks".

## PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:

Not flammable. Use of barrier cream and ventilation of the work area are recommended.

## DISPOSAL:

Do not allow dispersal into drains, sewers or ground. Rinse containers, which have been emptied from any residues, with little water and dispose of the containers in accordance with local guidelines as recyclable packaging. Collect and reuse rinsing water and product remnants. If even necessary, dispose of containers with residues as well as product remnants as special waste.